



ALABAMA DEPARTMENT OF TRANSPORTATION

1409 Coliseum Boulevard, Montgomery, Alabama 36130-3050

BUREAU OF MATERIALS AND TESTS

3700 Fairground Road, Montgomery, Alabama 36110

Telephone: 334-206-2200 FAX: 334-264-6263



Bob Riley
Governor

Joe McInnes
Transportation Director

March 10, 2006

TECHNICAL MEMORANDUM 95-06

To: Testing Manual Users

From: Larry Lockett
Materials and Tests Engineer

A handwritten signature in black ink that reads "Larry Lockett".

Re: Revisions to ALDOT Testing Manual
ALDOT-350, "In-Place Bituminous Plant Mix Density Measurements"

Please be advised that the above referenced procedure was revised on September 1, 2005. The revisions to the procedure were approved by FHWA on March 10, 2006.

The revisions include the following:

- a. Deletes Troxler Electronic Labs Model 4640-A and gauge operation instructions.
- b. The minimum number of cores taken and used to calibrate thin-layer or dual-purpose gauges has been reduced from five to four. Additionally, directs that these cores be used for determining the pay-factor of the test strip.

A copy of the revised section may be viewed in the Testing Manual available through the ALDOT homepage.

LL/RLW/wdb

cc: Mr. Lynn Wolfe
File