

Material Safety Data Sheet

Identity: Finn HydroStik

Section I-Product and Company Information

A500 Hydrostik, manufactured for Finn Corporation, 9281 LeSaint Dr. Fairfield, Ohio
45014 Information Phone (513)-874-2818

Section II-Composition/information on ingredients

Ingredient:	Guar Gum
CAS #:	900-30-0
% Weight:	90-100
Exposure Limits:	5 mg/m ³ (respirable) PEL-TWA 3 mg/m ³ (respirable) TLV-TWA 10 mg/m ³ (inhalable dust) TLV-TWA

Section III-Hazards Identification

Emergency Overview:

This product is a natural product. High concentration of dust suspended in the air present a fire and explosion hazard. Excessive inhalation of dust may cause respiratory irritation and possible lung injury with symptoms of shortness of breath and reduced lung function.

Acute Health Effects:

Eye contact: Contact may cause irritation based on studies with laboratory animals

Skin contact: Contact may cause dryness

Inhalation: Inhalation of dust may cause irritation of the nose, throat and respiratory passages. Symptoms include coughing, sore throat, nasal congestion, sneezing, wheezing and shortness of breath. May cause allergic reaction in susceptible individuals.

Ingestion: DO NOT INGEST. While this product is non-toxic by ingestion, swallowing small amounts could cause complete blockage of the mouth, pharynx, trachea, esophagus and/or gastrointestinal system which may cause choking, suffocation and/or other life threatening medical conditions. Get medical attention immediately.

Chronic Health Effects: Prolonged overexposure to any nuisance dust may cause lung injury. Symptoms include cough, shortness of breath and reduced pulmonary function.

Carcinogenicity: None of the components of this product are listed as carcinogens or suspected carcinogens by OSHA, IARC or NTP.

Medical Conditions Aggravated by Exposure: Persons with pre-existing skin and respiratory disorders may be at an increased risk from exposure.

Material Safety Data Sheet

Identity: Finn HydroStik

Section IV-First Aid Measures

Eye: Flush immediately with large amounts of water. Eyelids should be held away from the eyeball to ensure thorough rinsing. If irritation persists get medical attention.

Skin: No first aid should normally be needed. Wash exposed skin with soap and water after use. If irritation or rash develops get medical attention. Use skin lotion if dryness occurs.

Inhalation: If symptoms of irritation or allergy develop, remove person from source of exposure to fresh air. If symptoms persist get medical attention.

Ingestion: Swallowing even small amounts may have serious, life-threatening effects. Get immediate medical attention.

Section V-Firefighting Measures

Flash point:	Not applicable
Lower explosion limit:	0.04 az/cf
Autoignition temperature:	Not Determined
Upper explosion limit:	Not Determined

Extinguishing Media: Use water fog, dry chemical, carbon dioxide or foam. Do not use streams of water as dust dispersed by water streams can explode.

Special Fire Fighting Procedures: Wear positive pressure, self-contained breathing apparatus and full protective clothing.

Unusual Fire and Explosion Hazards: Powder has the potential to form explosive mixtures with air. Avoid creating dust. Keep away from heat, sparks, and open flames.

Combustion Products: Oxides of carbon and nitrogen

Section VI-Accidental Release Measures

Wear appropriate protective clothing and equipment. Sweep up or vacuum, avoiding the creation of airborne dusts, and collect into a suitable container for disposal. Keep spilled product away from flammable and combustible materials. Wash residual traces with hot water after clean-up is complete. Caution: guar gum is very slippery when wet.

To the best of our knowledge, the information contained herein is accurate. However, Finn Corporation assumes no liability whatsoever for the accuracy or completeness of the information contained herein.

Material Safety Data Sheet

Identity: Finn HydroStik

Section VII-Handling and Storage

Handling: Avoid generating and breathing dust. Avoid eye contact. Use with adequate local exhaust ventilation and dust collection to maintain the concentration of airborne dusts below the exposure limits. If clothing becomes contaminated, remove and launder before re-use. Wash thoroughly after handling.

Storage: Keep product dry. Store in a cool and dry area. Keep containers closed to avoid moisture absorption.

Section VIII-Exposure Controls/Personal Protection

Engineering Controls: Use explosion proof local exhaust ventilation as needed to maintain exposure concentrations below the recommended limits.

Personal Protective Equipment (PPE):

Eye Protection: Safety glasses or goggles recommended.

Skin Protection: Robber, plastic or leather gloves recommended.

Respiratory Protection: If the concentrations exceed the Threshold Value Limit (TLV), a NIOSH approved dust respirator, supplied air respirator or self-contained breathing apparatus is recommended. Select appropriate respiratory protection for the respirable particulates based on consideration of the airborne workplace concentrations and duration of exposure. Select and use respirators in accordance with 29 CFR 1910.134, ANSI Z88.2, the NIOSH Respirator Decision Logic and good industrial hygiene practice. <http://www.access.gpo.gov/nara/cfr/cfr-retrieve.html1#page1>, ANSI Z88.2 <http://www.ansi.org/>, the NIOSH Respirator Decision Logic an good industrial hygiene practice <http://www.cdc.gov/niosh/homepage.html>.

Section IX-Physical and Chemical Properties

Boiling point:	Not Applicable
Melting point:	Decomposes
Vapor pressure:	Not Applicable
% Solubility in water:	Complete
Odor/appearance:	Yellow powder with bean-like odor
Specific Gravity:	Not applicable
% volatile:	Not applicable
Evaporation rate (butyl acetate=1):	Not applicable
pH:	Not applicable
Octanol/water partition coefficient:	Not applicable

Material Safety Data Sheet

Identity: Finn HydroStik

Section X-Stability and Reactivity

Stability: Material is stable

Incompatibility: Avoid high temperatures, sparks, open flames and moisture. Avoid contact with strong oxidizing agents.

Hazardous Reactions-Decomposition Products: Combustion may produce carbon dioxide, carbon monoxide and oxides of nitrogen.

Hazardous Polymerization: Will not occur.

Section XI-Toxicological Information

Guar Gum: Oral rat LD50: 9.4g/kg

Guar gum is a natural food additive, although direct use in powder or pill form is banned by the FDA due to the risk of respiratory or gastrointestinal blockage.

Section XII-Ecological Information

No ecotoxicity data is available at this time.

Section XIII-Disposal Considerations

Dispose in compliance with all applicable federal, state and local regulations. Do not dump down sewers or drains as this may cause blockage.

Section XIV-Transport Information

U.S. Department of Transportation (DOT)

Proper shipping name:	No regulated
Hazard class:	N/A
UN/NA code:	N/A
Packing group:	N/A
Labels required:	N/A
IMDG code:	

Proper shipping name:	Not regulated
Hazard class:	N/A
UN/NA code:	N/A
Packing group:	N/A
Labels required:	N/A

Material Safety Data Sheet

Identity: Finn HydroStik

Section XV-Regulatory Information

U.S. Regulations

Comprehensive Environmental Reponse and Liability Act of 1980 (CERCLA)

Reportable Quantity:

This product is not subject to CERCLA reporting requirements as it is sold.

OSHA hazard categories: Irritant, sensitizer, combustible dust

Superfund Amendments and Reauthorization Act (SARA) Title III Information:

SARA Section 311/312 hazard categories: Fire Hazard, Acute Health

This product contains the following toxic chemical(s) subject to reporting requirements of SARA Section 313: None

California Proposition 65: This product is not known to contain chemical regulated under California Proposition 65.

Toxic Substances Control Act (TSCA): All components of this product are listed on the TSCA inventory or exempt from notification requirements.

European Inventory of Commercial Chemical Substances: All of the components of this product are listed on the EINECS Inventory or exempt from notification requirements.

Australian Inventory of Chemical Substances: All of the components of this product are listed on the EINECS inventory or exempt from notification requirements.

Canadian WHIMIS Classification: Class B, Division 4 (flammable solid)

Section XVI-Other Information

NFPA Ratings:

Health: 1 Flammability: 2 Reactivity: 0

HMIS Ratings:

Health: 1 Flammability: 2 Reactivity: 0

Abbreviations:

ACGIH	American Conference of Governmental Industrial Hygienists
ANSI	American National Standards Institute
CAS	Chemical Abstracts Service
CDC	Center for Disease Control and Prevention
CFR	The Code of Federal Regulations
EEC	European Economic Community
EINECS	European Inventory of Existing Commercial Chemical Substances
EPA	United States Environmental Protection Agency

Material Safety Data Sheet

Identity: Finn HydroStik

FDA	United states Food and Drug Administration
HMIS	Hazardous Material Identification System
IARC	International Agency for Research on Cancer
IMDG	International Maritime Dangerous Goods
LD50	Lethal Dose expected to cause death in 50% of the test animals
MITI	Ministry of International Trade and Industry
NFPA	National Fire Protection Association
NIOSH	CDC-National Institute for Occupational Safety
NTP	National Toxicological Program
OSHA	U.S. Department of Labor, Occupational safety and health administration
PEL	OSHA-permissible exposure limit
TLV	ACGIH-threshold
TWA	Time weighted average
UN/NA	United Nations/North America
US	United States
WHMIS	Workplace Hazardous Materials Information System



DESCRIPTION

FINN HydroStik is a special gum-based tackifier for a fast and effective method of controlling wind and water erosion of mulch and soil. HydroStik contains dispersion agents allowing it to mix easily into suspension and is effective in HydroSeeding or straw tacking slurries. HydroStik also lubricates the materials in the HydroSeeder® tank for improved spraying performance. FINN HydroStik creates a fiber-to-soil bond. Used for normal to moderate slope conditions.

APPLICATION & RATES

FIBER MULCH TACKING.....	40 lbs. per acre for normal slopes
	60 lbs. per acre for >2:1 slopes
STRAW/HAY MULCH BINDING.....	30 lbs. per acre
SOIL STABILIZATION.....	40 lbs. per acre
	60 lbs. per acre for > 2:1 slopes
MULCH SLURRY LUBRICANT.....	1 lb. per 100 lbs. of mulch

PRODUCT REQUIREMENTS

N/A

PACKAGING

40 LB . CASE (8-5 LB. BAGS)

50 LB. BAG