## TRAFFIC CONTROL PLAN NOTES

- FISCAL SHEET YEAR NO.

- - 29. THE LIMITS OF THE WORK AREA SHALL BE DETERMINED BY THE ENGINEER, BUT IN NO CASE SHALL THE WORK LIMITS EXCEED THE LENGTH OF  $\frac{1}{2}$  DAY'S PLANNED OPERATION OR ONE MILE, WHICHEVER IS LESS.
  - 30. THE G20-1 AND G-20-2 SIGNS ARE NOT REQUIRED FOR PROJECTS LESS THAN 2 MILES IN LENGTH. WHEN G20-1 AND G20-2 SIGNS ARE NOT USED, THE R16-3 SIGNS SHALL BE PLACED 500 FT IN ADVANCE OF THE "ROAD WORK 1500 FT" SIGNS AND THE R16-3 SIGNS SHALL BE PLACED 250 FT PAST THE TERMINATION OF THE LANE CLOSURE AS INDICATED IN THE TRAFFIC CONTROL PLAN. R16-3 (HIGHER FINE ZONE) SIGNS SHALL BE POSTED AT MAXIMUM INTERVALS OF 3 MILES THROUGHOUT THE PROJECT LIMITS.
- - 32. ONE W20-1 SIGN (ROAD WORK 500 FT) HAS BEEN SET UP TO BE USED AT EACH INTERSECTING STREET OR ROAD. A W20-1 (STD.) SIGN (3' X 3') SHOULD BE USED FOR LOW VOLUME, LOW SPEED INTERSECTING STREETS / ROADS. A W20-1 (EXPRY./FRWY.) SIGN (4' X 4') SHOULD BE USED FOR HIGH VOLUME, HIGH SPEED INTERSECTING STREETS / ROADS.
  - 33. IF THE CONTRACTOR CHOOSES TO SPLICE THE REQUIRED POST MOUNTED CONSTRUCTION SIGNS, THEY SHALL BE SPLICED AS SHOWN ON SPECIAL DRAWING IHS-710-23.

REVISIONS		
DRAWN - 01/05/07		ALABAMA DEPARTMENT
CHANGED BUREAU NAME 10/6/17		OF TRANSPORTATION
12/5/18 DELETED NOTE 30		LOCAL TRANSPORTATION
7/31/19- REVISED NOTE 31		BUREAU
		TRAFFIC CONTROL PLAN
9/3/19- REVISED NOTE 29		STANDARD NOTE SHEET
4/13/21 - ADDED NOTE 30		
11/15/21 - REVISED NOTE 30		NOT TO SCALE